## Coaxial Audio IR Dome Camera





## Specification

Resolution	5MP
Image Sensor	1/2.5" CMOS 5Mega sensor
Effective pixels	2592(H) x 1944(V)
Video Mode	TVI
Audio	TVI mode support Coaxial Audio transmit
Audio pick-up distance	MIC-S/N Ratio -62db ≈ 5.0M
Video Resolution & Frame Rate	5MP 20FPS/12.5FPS 2MP 30FPS/25FPS NTSC/PAL
UTC Coaxial Control	Support UTC function
Wide Dynamic Range	DWDR
White balance	Auto White balance
Day/Night Mode	Outside (External control)
Auto Exposure	Brightness / Exposure Mode (Global, BLC, Center) / Anti Flicker
Digital Noise Reduction	2DNR
IR Range	2pcs Array Led ; 20M IR distance
Intelligent Infrared	Support Intelligent Infrared (Avoid Overexposing)
Signal to Noise Ratio	More than 50dB
OSD Menu	AE / AWB / Day & Night / Image Enhance / Video Setting / Language / LED
Image Enhance	Contrast, Sharpness, Saturate, 2DNR, DWDR
Lens	5MP / 3.6mm ICR Lens
Min. illumination	0.03 Lux @F1.2
Working Environment	Temperature -20°C $\sim$ 70°C , Humidity 0 $\sim$ 90% RHG
Dimension / Weight	100(Ø) x 77(H) mm / 160g.
Power Consumption	DC12V