

2MP Network Bullet Camera

30M IR



Specification

Model		IB23A3-F3	IB23R3-F3
SoC Brand		Taiwan NOVATEK SoC	
Image Sensor		1/2.7" 2MP CMOS Sensor	
Compression		Audio: G711	
Onvif		Profile S / Profile T	
Video Stream	Main	50Hz:25fps / 60Hz:30fps @ (1920x1080, 1280x720, 960x540, 704x480, 640x360)	
	Sub	50Hz:25fps / 60Hz:30fps @ (704x480, 640x360, 352x240, 320x180)	
	Third	50Hz:25fps / 60Hz:30fps @ (352x240)	
Video Bit Rate		64Kbps-8Mbps, Support CBR-VBR	
Wide Dynamic Range		HDR Mode up to 100dB (Normal), Linear Mode 82dB (Off)	
Digital Zoom		Yes	
White Balance		Auto / Indoor / Outdoor / Manual	
Day/Night		Auto / Day mode / Night mode / External control	
Shutter / Exposure Model		Auto / 1/30(25) ~ 1/10000	
Digital Noise Reduction		2DNR 、 3DNR	
OSD Display		Camera name/ Date and Time, Display position can be adjusted	
Image Settings	Brightness, Saturation, Contrast, Sharpness, Image Enhancement, Anti-flicker		
	Flip Mode Adjustable by Client Software or Web Browser		
Watermark		Yes	
ICR Lens		3.6mm 3MP Lens (6mm optional)	
Min. illumination		0.01 Lux @F1.2 ; 0 Lux @F1.2 (IR On)	
IR Range		30M IR distance	
ROI (Region of Interest)		4 Zones	
Privacy Mask		8 Zones	
Audio In / Out	Mic. in		Mic. in
	No		Speaker out (optional)
Alarm In / Out		No	
SD card Storage		No	
Intelligent Detection Function		Motion Detection Optional: Video Tampering	
Network Interface		10M / 100M Base-TX Ethernet	
Protocol		IPv4/HTTP/ HTTPS/ SMTP/DNS/DDNS/RTSP/TCP/UDP/DHCP/RTP/NTP/ARP/P2P	
Maximum connection stream		10	
Browser		Edge / Chrome	
Remote		PC support Windows 11/10/8/7, App for Mac/iPhone/iPad/Android phone and Tablet PC	
POE (Power over Ethernet)		Build-in ; IEEE802.3af	
Waterproof		IP66	
Working Environment		-25℃ ~ 65℃, 0 ~ 90% RHG	
Dimension / Weight		74(W) x 68(H) x 108 (L) mm / 600g.	
Power Consumption		12 VDC, max. 7W	